



MATERIAL SAFETY DATA SHEET

Quarry Products – Sand & Gravel

STATEMENT OF HAZARDOUS NATURE

This product is classified as hazardous according to the criteria of the National Occupational Health and Safety Commission (NOHSC).

PF Formation
 ABN 62 113 814 256
 1774 Wisemans Ferry Road
 Maroota NSW 2756
 Australia

Telephone: +61 2 4566 8314
 Facsimile: +61 2 4566 8349

IMPORTANT NOTICE: This Material Data Sheet (MSDS) is issued by PF Formation, in accordance with National Occupational Health & Safety Commission (NOHSC) guidelines. As such, the information in it must not be altered, deleted or added to. PF Formation will issue a new MSDS when there is a change in product specifications and/or NOHSC guidelines/regulations. PF Formation will not accept any responsibility for any changes made to its MSDS by any other person or organisation.

Product Name:	Maroota Quarry Products
Other Names:	Sand, Filling Sand, Maroota 5mm Gold, 10mm Pea Gravel, Brickie Sand, Coarse Sand, Red Sand, White clay, 30mm sandstone
Manufacturer's Product Code:	Not Applicable
UN Number:	None Allocated
Dangerous Goods Class & Subsidiary Risk:	N/A
Hazchem Code:	N/A
Poisons Schedule Number:	Not Scheduled

PRODUCT DESCRIPTION/PROPERTIES

Appearance:	Shape and texture varies from smooth and rounded to angular and rough. White/Yellow/Red in colour.
Boiling Point:	N/A
Melting Point:	N/A
Vapor Pressure:	N/A
Assumed Specific Gravity:	2.0 to 3.0
Flashpoint:	N/A
Flammability Limits:	Not Flammable
Solubility in Water:	Not Soluble

Use:
 Construction, concrete and general fill.

PROGRAM No.	VERSION	APPROVED	PROGRAM NAME	PAGE No	REVIEW DATE
1	V2	Joshua Graham	MSDS for Sand & Gravel	1	17.05.2021

OTHER PROPERTIES

pH: 4.5 to 6.5
Bulk Density: minimum 1.2 (t/m³)
Odour: Normally no odour

Ingredients:

Naturally occurring material excavated or a blend of materials and processed at the quarry. Depending upon the source materials, the crystalline silica (quartz) content of any particular quarry product can range from zero % to 100%.

Quartz CAS No – 14808-80-7 Proportion – 0.1-100%

Note: Quartz is a natural constituent of most rocks, the amount depends on the rock type.

HEALTH HAZARD INFORMATION***Acute Health Effects***

Swallowed: Ingestion is unlikely under normal conditions of use, however swallowing of quarry products may result in abdominal discomfort and possibly increase the risk of gastro-intestinal infections.

Eye: Dust from this product may irritate eyes causing watering and redness.

Skin: Dust from this product may be irritating and abrasive to the skin

Inhaled: Dust may irritate nose, throat and respiratory tract and can exacerbate pre-existing conditions such as asthma and bronchitis.

Chronic Health Effects

Repeated inhalation of these products may lead to respiratory irritation, inflammation or sensitisation. Because Quarry Products may contain crystalline silica, repeated inhalation of high concentrations of respirable dust may cause scarring of the lung (silicosis), lung cancer, and chronic bronchitis. It is not recommended to repeatedly swallow this material or repeatedly allow it to come into contact with eyes.

FIRST AID

Swallowed: The patient should be given water to drink and consult a doctor if abdominal symptoms persist.

Eye: Flush eyes thoroughly with running water for at least ten minutes. If irritation or redness persist, seek medical attention.

Skin: Wash affected area thoroughly with mild soap and water. Clean abrasions and cuts and apply a sterile dressing.

Inhaled: Remove patient to fresh air. If respiratory irritation, dizziness or nausea occurs, seek immediate medical assistance.

FIRST AID FACILITIES

Eye wash station and suitable facilities available to carry out the first aid procedures outlined above.

ADVICE TO DOCTOR

Treat symptomatically.

PROGRAM No.	VERSION	APPROVED	PROGRAM NAME	PAGE No	REVIEW DATE
1	V2	Joshua Graham	MSDS for Sand & Gravel	2	17.05.2021

PRECAUTIONS FOR USE

- Exposure Standards:** There is no specific standard for Quarry Products. However Worksafe Australia Exposure Standard:
Silica-crystalline: 0.05 mg/cubic metre time-weighted average (TWA). Inspirable dust NOS (not otherwise specified: 10mg/cubic metre time-weighted average (TWA) for dust containing 0.5% or less of crystalline-silica. (Inspirable dust is equal to or less than 180 micron size).
- Engineering Controls:** Any involvement with these products should be conducted in a way as to avoid contact with the skin and eyes as well as swallowing and inhalation. Keep exposure to dust as low as practicable, with the aim of maintaining respirable crystalline silica dust levels to below 0.05 mg/m³ TWA. Work in open air and the opening or external openings (such as doors and windows in buildings) generally provides adequate ventilation.
- Special Considerations for Repairs/Maintenance:** Avoid breathing dust. Where possible vacuum or wash down all gear, equipment or mobile plant prior to maintenance and repair work. If compressed air cleaning cannot be avoided, wear eye and respiratory protection, and clothing as listed below.

PERSONAL PROTECTION

- Skin Protection:** Wear loose comfortable clothing and boots and standard duty leather or equivalent gloves. Long sleeved shirts and long trousers are recommended if a skin irritation occurs or a person has a history of skin conditions. All work clothes should be washed regularly. Clothing according to AS 2161.
- Respiratory Protection:** When exposed to dust an approved respirator should be worn that is suitable for respirable particulate and which conforms with AS/NZS 1715 and AS/NZS 1716. The standards should be followed in the selection, fit testing, use, storage and maintenance of the respiratory equipment.
- Eye Protection:** Dust resistant non-fogging safety goggles or glasses (AS/NZS 1336) should be worn if exposed to dust.

FLAMMABILITY

Quarry products are not flammable, do not support combustion of other materials, and do not cause dust explosions.

PROGRAM No.	VERSION	APPROVED	PROGRAM NAME	PAGE No	REVIEW DATE
1	V2	Joshua Graham	MSDS for Sand & Gravel	3	17.05.2021

SAFE HANDLINE AND STORAGE

- Storage and Transport:** Avoid breathing dust. Respirable dusts may be generated during processing, handling, and storage. Use proper control measures, including ventilation, enclosure of materials, covering loads on trucks and wetting down material whilst in use. When stockpiling and handling large quantities of quarry products, care should be taken to avoid having the faces of the stockpile steeper than the natural angle of repose of the material. Steep faces can fall without warning and trap persons resulting in injury and possible suffocation. When transporting by road, all loads should be covered.
- Spills and Disposal:** Spilled material should be wet down with water to reduce dust generation before cleanup. Clean Quarry materials can be reused, otherwise dispose of waste quarry materials in accordance with local authority guidelines.
- Fire/Explosion Hazard:** Quarry products are non flammable.

OTHER INFORMATION

- Smoking and other dusts:** Smoking increases the risk of occupational respiratory diseases. It is recommended that all storage and work areas should be smoke-free zones.

CONTACT POINT

Title: Weighbridge
 Telephone: +61 2 4566 8314
 Review Date: 17th May 2021

DISCLAIMER - Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

PROGRAM No.	VERSION	APPROVED	PROGRAM NAME	PAGE No	REVIEW DATE
1	V2	Joshua Graham	MSDS for Sand & Gravel	4	17.05.2021